

KENWOOD

Listen to the Future

NEXEDGE®

NX-220/320

NEXEDGE® VHF/UHF Digital & FM Portable Radios

NXDN®

FleetSync®
by KENWOOD

● GENERAL FEATURES

- 5 W (136-174 MHz) Models
- 5 W (400-470, 450-520 MHz) Models
- 260 CH-GID / 128 Zones (LCD Models)
- 64 CH-GID / 4 Zones (Non LCD Models)
- 12-Key Keypad Models
- 8 Character Alphanumeric Aliases
- Backlit LCD & Keys
- Function / Status LCD Icons
- Transmit / Busy / Call Alert / Warn LED
- On / Off Volume Knob
- 16-Position Mechanical Selector
- 4 Front PF Keys (LCD Models)
- 3 Side PF Keys
- Emergency / AUX Key
- Built-in Motion Sensor
- 500 mW Speaker Audio
- Zone / CH Number Voice Announcement
- KMC-48GPS Speaker Mic Option
- KPG-141D Windows® FPU
- Flash Firmware Upgrading
- MIL-STD-810 C/D/E/F/G
- IP54/55 Water & Dust Intrusion
- PC Serial Interface
- SDM Manual Input*¹
- Transparent Data Mode*¹

● DIGITAL – GENERAL

- NXDN® Digital Air Interface
- AMBE+2™ VOCODER
- 6.25 & 12.5 kHz Channels
- Over-the-Air Alias
- Over-the-Air Programming
- Paging Call
- Emergency Call
- All Group Call
- Status Messaging*¹ *²
- Remote Stun / Kill*¹
- Remote Check*¹
- Short & Long Data Messages*¹
- GPS Location with Voice*¹
- NXDN® Scrambler Included

● DIGITAL – CONVENTIONAL MODE

- 64 Radio Access Numbers (RAN)
- Individual & Group Selective Call*³
- Mixed FM / Digital Operation
- Conventional IP Networks
- Site Roaming

● DIGITAL – TRUNKING MODE

- Individual Private Call
- Group Call & Broadcast Call
- Telephone Interconnect
- Transmission Trunked Mode*⁴
- Message Trunked Mode*⁴
- Call Queuing with Priority*⁴
- Late Entry (UID & GID)*⁴
- 4 Priority Monitor ID's*⁴
- Remote Group Add*¹
- Failsoft Mode

● MULTI-SITE IP NETWORK COMPATIBLE

- 60,000 GIDs / UIDs
- Wide Area Group Call
- Auto Roaming Registration
- Group Registration

● SCAN

- Single Zone / Multi-Zone / List Scan
- Single Priority Scan (Conventional)

● FM MODES – GENERAL

- 25 & 12.5 kHz Channels
- Conventional & LTR® Zones
- FleetSync® / II, MDC-1200, DTMF*³
- QT / DQT & 2-Tone (Conventional Zones only)*³
- Voice Inversion Scrambler (16 Codes)

● FleetSync® / II (FM)

- PTT ID ANI / Caller ID*³
- Selective / Group Call*³
- Emergency, Status & Text Messages*¹

● MDC-1200

- PTT ID ANI / Caller ID*³
- Emergency, Radio Check & Inhibit

*¹ Requires NX subscriber unit PC Serial Interface compatible software application (e.g. Kenwood AVL & Dispatch Messaging software) or hardware (e.g. console).

*² Non LCD Models -Pre-programmed key operation

*³ Non LCD Models -Some screen / key-based functions are not available.

*⁴ These trunked features are primarily system programming and operational dependent. Priority Monitor also requires NX subscriber settings.



Options

■ KNB-55L
Li-Ion Battery
(1480mAh)



KNB-55L

■ KNB-56N
Ni-MH Battery
(1400mAh)

■ KNB-57L
Li-Ion Battery
(2000mAh)



■ KBP-5
6 AA Alkaline
Battery Case

■ KSC-25
Rapid Charger



KSC-25

■ KSC-30
Regular Charger
for Ni-MH Batteries

■ KSC-256
Rapid Rate 6-Unit
Charger



■ KMC-45
Speaker Microphone



KMC-45

■ KMC-21
Speaker Microphone

■ KMC-48GPS
GPS Speaker
Microphone



■ KMB-30
Wall Mount Bracket
for KSC-256



■ KRA-22/23
VHF/UHF Helical
Antenna



■ KRA-26/27
VHF Helical/
UHF Whip Antenna



■ KEP-2
2.5mm Earphone
Kit for KMC-45




■ KHS-7/7A
Single Muff Headset



KHS-7/7A

■ KHS-8BE/BL
2-wire Palm Mic.
w/Earphone



■ KHS-9BE/BL
3-wire Palm Mic.
w/Earphone



KHS-21

■ KHS-21
Headset w/Boom Mic.
& PTT

■ KHS-26
Clip Mic. w/Earphone



■ KHS-27
D-ring Earhanger
w/PTT & Mic.



■ KBH-12
Belt clip



All accessories and options may not be available in all markets. Contact an authorized Kenwood dealer for details and complete list of all accessories and options.

Main Specifications

		NX-220	NX-320
GENERAL			
Frequency Range	Type 1 Type 2	136-174 MHz	450-520 MHz 400-470 MHz
Number of Channels	LCD models	260 ch	
	Non LCD models	64 ch	
Zones	LCD models	128 zone	
	Non LCD models	4 zone	
Max. Channels per Zone	LCD models	250 ch	
	Non LCD models	16 ch	
Channel Spacing	Analog	12.5 / 15 / 25 / 30 kHz	12.5 / 25 kHz
	Digital	6.25 / 12.5 kHz	6.25 / 12.5 kHz
Operating Voltage		7.5 V DC ± 20%	
Battery Life (5-5-90)	KNB-55L (1480 mAh)	Approx. 8.5 hours	
	KNB-56N (1400 mAh)	Approx. 8.5 hours	
	KNB-57L (2000 mAh)	Approx. 11.5 hours	
		-30° C to +60° C	
Operating Temperature Range		± 2.0 ppm	
Frequency Stability		± 1.0 ppm	
Antenna Impedance		50 Ω	
Dimensions (W x H x D)	Projections not included LCD models	56.0 x 110.5 x 36.9 mm (radio only) 56.0 x 110.5 x 37.5 mm (with KNB-55L) 56.0 x 110.5 x 39.5 mm (with KNB-57L)	
	Non LCD models	56.0 x 110.5 x 37.5 mm (radio only) 56.0 x 110.5 x 38.1 mm (with KNB-55L) 56.0 x 110.5 x 40.1 mm (with KNB-57L)	
Weight (net)	LCD models	210 g (radio only) 305 g (with KNB-55L) 330 g (with KNB-57L)	
		205 g (radio only) 300 g (with KNB-55L) 325 g (with KNB-57L)	
	Non LCD models		

		NX-220	NX-320
RECEIVER			
Sensitivity	Digital @ 6.25kHz (3% BER)	0.20 μV	
	Digital @ 12.5kHz (3% BER)	0.25 μV	
	Analog (12dB SINAD)	0.25 μV	
Selectivity	Analog @ 25 kHz	72 dB	
	Analog @ 12.5 kHz	65 dB	
Intermodulation Distortion	Analog	70 dB	
Spurious Response	Analog	70 dB	
Audio Distortion		Less than 3%	
Audio Output		500 mW / 8 Ω	
TRANSMITTER			
RF Power Output		5 W / 1 W	
Spurious Response		70 dB	
FM Hum & Noise	Analog @ 25 kHz	45 dB	
	Analog @ 12.5 kHz	40 dB	
Audio Distortion		Less than 3%	
Modulation		16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Analog measurements made per TIA/EIA 603 and specifications shown are typical. Kenwood reserves the right to change specifications without prior notice or obligation.

FleetSync® is a registered trademark of Kenwood Corporation.

LTR® is a registered trademark of Transcript International.

AMBE+2™ is a trademark of Digital Voice Systems Inc.

Windows® is a registered trademark of Microsoft Corporation.

NXDN® is a registered trademark of Kenwood Corporation and Icom Inc.

NEXEDGE® is a registered trademark of Kenwood Corporation.

Applicable MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection	IP54/55				

To meet MIL-810 and IP grade, the 2-pin connector has to be connected.

Listen to the Future

Kenwood has always connected with people through sound. Now we want to expand the world of sound in ways that only Kenwood can, listening to our customers and to the pulse of the coming age as we head toward a future of shared discovery, inspiration and enjoyment.

Kenwood Corporation

1-16-2 Hakusan, Midori-ku, Yokohama-shi, Kanagawa, 226-8525 Japan

www.kenwood.com

http://nexedge.kenwood.com



ISO9001 Registered
Communications Equipment Division
Kenwood Corporation
ISO9001 certification

CL702KM-E-2